Languages

Languages

A language is a set of strings

String: A sequence of letters

Examples: "cat", "dog", "house", …

Defined over an alphabet:

$$\Sigma = \{a, b, c, \ldots, z\}$$

Alphabets and Strings

We will use small alphabets: $\Sigma = \{a, b\}$

Strings

a

ab $\quad u = ab$

$abba$ $\quad v = bbbaaa$

$baba$ $\quad w = abba$

$aaabbbaabab$

String Operations

$w = a_1 a_2 \cdots a_n$ $\qquad$ $abba$

$v = b_1 b_2 \cdots b_m$ $\qquad$ $bbbaaa$

Concatenation

$wv = a_1 a_2 \cdots a_n b_1 b_2 \cdots b_m$ $\qquad$ $abbabbbaaa$

$$w = a_1 a_2 \cdots a_n \qquad\qquad ababaaabbb$$

Reverse

$$w^R = a_n \cdots a_2 a_1 \qquad\qquad bbbaaababa$$

String Length

$$w = a_1 a_2 \cdots a_n$$

Length: $|w| = n$

Examples:

$$|abba| = 4$$

$$|aa| = 2$$

$$|a| = 1$$

Recursive Definition of Length

For any letter: $|a| = 1$

For any string wa: $|wa| = |w| + 1$

Example: $|abba| = |abb| + 1$

$= |ab| + 1 + 1$

$= |a| + 1 + 1 + 1$

$= 1 + 1 + 1 + 1$

$= 4$

Length of Concatenation

$$|uv| = |u| + |v|$$

Example: $u = aab, \quad |u| = 3$

$v = abaab, \quad |v| = 5$

$$|uv| = |aababaaab| = 8$$

$$|uv| = |u| + |v| = 3 + 5 = 8$$

Proof of Concatenation Length

Claim: $|uv| = |u| + |v|$

Proof: By induction on the length $|v|$

Induction basis: $|v| = 1$

From definition of length:

$$|uv| = |u| + 1 = |u| + |v|$$

Inductive hypothesis: $|uv| = |u| + |v|$

for $|v| = 1,2,\ldots,n$

Inductive step: we will prove $|uv| = |u| + |v|$

for $|v| = n+1$

Inductive Step

Write $v = wa,$ where $|w| = n, \quad |a| = 1$

From definition of length: $|uv| = |uwa| = |uw| + 1$

$$|wa| = |w| + 1$$

From inductive hypothesis: $|uw| = |u| + |w|$

Thus: $|uv| = |u| + |w| + 1 = |u| + |wa| = |u| + |v|$

Empty String

A string with no letters: λ

Observations: $|\lambda| = 0$

$$\lambda w = w\lambda = w$$

$$\lambda abba = abba\lambda = abba$$

Substring

Substring of string:

a subsequence of consecutive characters

String	Substring
$abbab$	ab
$abbab$	$abba$
$abbab$	b
$abbab$	$bbab$

Prefix and Suffix

$abbab$

Prefixes	Suffixes
λ	$abbab$
a	$bbab$
ab	bab
abb	ab
$abba$	b
$abbab$	λ



Another Operation

$$w^n = \underbrace{ww\cdots w}_{n}$$

Example: $(abba)^2 = abbaabba$

Definition: $w^0 = \lambda$

$$(abba)^0 = \lambda$$

The * Operation

Σ^* : the set of all possible strings from alphabet Σ

$$\Sigma = \{a, b\}$$

$$\Sigma^* = \{\lambda, a, b, aa, ab, ba, bb, aaa, aab, \ldots\}$$

The + Operation

Σ^+ : the set of all possible strings from alphabet Σ except λ

$$\Sigma = \{a, b\}$$

$$\Sigma^* = \{\lambda, a, b, aa, ab, ba, bb, aaa, aab, \ldots\}$$

$$\Sigma^+ = \Sigma^* - \lambda$$

$$\Sigma^+ = \{a, b, aa, ab, ba, bb, aaa, aab, \ldots\}$$

Language

A language is any subset of Σ^*

Example: $\Sigma = \{a, b\}$

$$\Sigma^* = \{\lambda, a, b, aa, ab, ba, bb, aaa, \ldots\}$$

Languages: $\{\lambda\}$

$$\{a, aa, aab\}$$

$$\{\lambda, abba, baba, aa, ab, aaaaaa\}$$

Another Example

An infinite language $L = \{a^n b^n : n \geq 0\}$

λ

ab

$aabb$

$aaaaabbbbb$

$\in L$

$abb \notin L$

Operations on Languages

The usual set operations

$$\{a, ab, aaaa\} \cup \{bb, ab\} = \{a, ab, bb, aaaa\}$$

$$\{a, ab, aaaa\} \cap \{bb, ab\} = \{ab\}$$

$$\{a, ab, aaaa\} - \{bb, ab\} = \{a, aaaa\}$$

Complement: $\overline{L} = \Sigma^* - L$

$$\overline{\{a, ba\}} = \{\lambda, b, aa, ab, bb, aaa, \ldots\}$$

Reverse

Definition: $L^R = \{w^R : w \in L\}$

Examples: $\{ab, aab, baba\}^R = \{ba, baa, abab\}$

$$L = \{a^n b^n : n \geq 0\}$$

$$L^R = \{b^n a^n : n \geq 0\}$$

Concatenation

Definition: $L_1 L_2 = \{xy : x \in L_1, y \in L_2\}$

Example: $\{a, ab, ba\}\{b, aa\}$

$= \{ab, aaa, abb, abaa, bab, baaa\}$

Another Operation

Definition: $L^n = \underbrace{LL\cdots L}_{n}$

$$\{a,b\}^3 = \{a,b\}\{a,b\}\{a,b\} =$$

$$\{aaa, aab, aba, abb, baa, bab, bba, bbb\}$$

Special case: $L^0 = \{\lambda\}$

$$\{a, bba, aaa\}^0 = \{\lambda\}$$

More Examples

$$L = \{a^n b^n : n \geq 0\}$$

$$L^2 = \{a^n b^n a^m b^m : n, m \geq 0\}$$

$$aabbaaabbb \in L^2$$

Star-Closure (Kleene *)

Definition: $L^* = L^0 \bigcup L^1 \bigcup L^2 \cdots$

Example:

$$\{a,bb\}^* = \begin{Bmatrix} \lambda, \\ a, bb, \\ aa, abb, bba, bbbb, \\ aaa, aabb, abba, abbbb, \ldots \end{Bmatrix}$$

Positive Closure

Definition: $L^+ = L^1 \cup L^2 \cup \cdots$

$= L^* - \{\lambda\}$

$$\{a, bb\}^+ = \begin{Bmatrix} a, bb, \\ aa, abb, bba, bbbb, \\ aaa, aabb, abba, abbbb, \ldots \end{Bmatrix}$$

Finite Automata

Finite Automaton



Finite Accepter



Transition Graph



Initial Configuration



Reading the Input






a
b
b
a
a, b
q5
b
a
a
b
a, b
q0
a
q1
b
q2
b
q3
a
q4


a
b
b
a
a, b
q5
b
a
a
b
a, b
q0
a
q1
b
q2
b
q3
a
q4


a b b a
a, b
q5
b
a
a
b
a, b
q0
a
q1
b
q2
b
q3
a
q4



Output: "accept"

Rejection




a
b
a
a, b
q5
b
a
a
b
a, b
q0
a
q1
b
q2
b
q3
a
q4


a
b
a
a, b
q5
b
a
a
b
a, b
q0
a
q1
b
q2
b
q3
a
q4

a
b
a


a, b
q5
b
a
a
b
a, b
q0
a
q1
b
q2
b
q3
a
q4


a
b
a
a, b
Output:
"reject"
q5
b
a
a
b
a, b
q0
a
q1
b
q2
b
q3
a
q4

Another Example






a
a
b


a
a, b
b
a, b
q0
q1
q2


a
a
b


a
a, b
b
a, b
q_0
q_1
q_2

a
a
b


a
a, b
b
a, b
q0
q1
q2

a
a
b


a
a, b
Output: "accept"
b
a, b
q_0
q_1
q_2

Rejection





b
a
b


a
a, b
b
a, b
q_0
q_1
q_2

b
a
b


a
a, b
b
a, b
q_0
q_1
q_2


b
a
b


a
a, b
b
a, b
q0
q1
q2



Output: "reject"

Formalities

Deterministic Finite Accepter (DFA)

$$M = (Q, \Sigma, \delta, q_0, F)$$

Q : set of states

Σ : input alphabet

δ : transition function

q_0 : initial state

F : set of final states

Input Aplhabet Σ

$$\Sigma = \{a, b\}$$



Set of States Q

$$Q = \{q_0, q_1, q_2, q_3, q_4, q_5\}$$



Initial State q_0



Set of Final States F

$$F = \{q_4\}$$



Transition Function δ

$$\delta : Q \times \Sigma \to Q$$



$$\delta(q_0, a) = q_1$$



$$\delta(q_0, b) = q_5$$



$$\delta(q_2, b) = q_3$$



Transition Function δ

δ	a	b
q_0	q_1	q_5
q_1	q_5	q_2
q_2	q_2	q_3
q_3	q_4	q_5
q_4	q_5	q_5
q_5	q_5	q_5



Extended Transition Function δ^*

$$\delta^* : Q \times \Sigma^* \to Q$$



$$\delta^*(q_0, ab) = q_2$$



$$\delta^*(q_0, abba) = q_4$$



$$\delta^*(q_0, abbbaa) = q_5$$



Observation: There is a walk from q_0 to q_1 with label $abbbaa$

$$\delta^*(q_0, abbbaa) = q_5$$



Recursive Definition

$$\delta^*(q,\lambda) = q$$

$$\delta^*(q,wa) = \delta(\delta^*(q,w),a)$$



$$\delta^*(q_0, ab) =$$

$$\delta(\delta^*(q_0, a), b) =$$

$$\delta(\delta(\delta^*(q_0, \lambda), a), b) =$$

$$\delta(\delta(q_0, a), b) =$$

$$\delta(q_1, b) =$$

$$q_2$$



Languages Accepted by DFAs

Take DFA M

Definition:

The language $L(M)$ contains all input strings accepted by M

$L(M)$ = { strings that drive M to a final state}

Example

$L(M) = \{abba\}$

M



Another Example

$L(M)=\{\lambda, ab, abba\}$

M



Formally

For a DFA $M = (Q, \Sigma, \delta, q_0, F)$

Language accepted by M :

$$L(M) = \{w \in \Sigma^* : \delta^*(q_0, w) \in F\}$$



Observation

Language accepted by M:

$$L(M)=\{w\in\Sigma^*:\delta^*(q_0,w)\in F\}$$

Language rejected by M:

$$\overline{L(M)}=\{w\in\Sigma^*:\delta^*(q_0,w)\notin F\}$$

More Examples

$$L(M) = \{a^n b : n \geq 0\}$$



$L(M)$= { all substrings with prefix ab }



$L(M)$ = { all strings without substring 001 }



Regular Languages

A language L is regular if there is a DFA M such that $L = L(M)$

All regular languages form a language family

Example

The language is regular: $L = \{awa : w \in \{a,b\}^*\}$